

The Road Warrior Bracelet

Project B108

Designer: Andrea Morici

Where would any rugged man be without his Road Warrior Necklace and its partner, this handsome bracelet?




What You'll Need

Beadsmith Dark Brown Faux Leather Suede Beading Cord 9Ft (3 Yd) Spool
SKU: XCR-43105
Project uses 16 inches



Paint Brush Desert Jasper 6mm Heishe Beads 15.5 Inch Strand
SKU: SPJA-191
Project uses 10 pieces



Fine Silver Plated Flat Round Textured 2 Hole Disc Connector Bead 20mm (2)
SKU: BMB-3806
Project uses 1 piece




Vintaj Natural Brass Mini Dog Tag Pendant Charms 24mm (2)
SKU: PND-7175
Project uses 1 piece



Real Black Lava 10mm Round Beads 15.5 Inch Strand
SKU: SPLV-20
Project uses 1 piece



Fine Silver Plated Pewter Maldive Larin Coin Charm 9.5mm (2)
SKU: PND-5170
Project uses 1 piece



Beadalon Silver Plated Crimp Tubes 1.3mm (75 Beads)
SKU: FCR-1215
Project uses 2 pieces



Silver Plated Open Jump Rings 7mm 20 Gauge (x100)
SKU: FJR-5170
Project uses 4 pieces



Soft Touch Best Beading Wire .019 Inch 30Ft Soft Flex
SKU: XCR-5493
Project uses 3 inches



Silver Plated Head Pins 2 Inches/21 Gauge (X50)
SKU: FHP-5325
Project uses 1 piece



Vintaj Natural Brass Jump Rings 7.25mm Open 16 Gauge (20)
SKU: FJR-5372
Project uses 6 pieces



Instructions:

1. Cut a piece of Soft Flex beading wire at three inches long. Set aside.
2. Thread a silver jump ring through the hole on the small coin pendant, and close the jump ring.
3. Thread a brass jump ring through the hole on the brass dog tag and close the jump ring.
4. Thread a lava bead onto a headpin, make a simple loop and trim off excess wire. Add a silver jump ring to the loop on that headpin.
5. Secure one end of the beading wire with a bead stopper, and onto the wire thread the following: two desert jasper heishe beads, the small coin pendant, three more jasper heishe beads, the brass dog tag, three more jasper heishe beads, the lava bead drop, and two more heishe beads.
6. Thread a crimp bead onto the end of the wire, but do not crimp it yet.
7. Thread the end of the wire through one of the holes of the flat round textured connector disc, and back through the crimp bead. Crimp the crimp bead, and trim off excess wire on that side.
8. To the other hole of the flat round textured connector disc, add a brass jump ring.
9. Remove the bead stopper from the other end of the wire and add a crimp bead, but don't crimp yet.
10. Thread the wire through a brass jump ring and back through the crimp bead and crimp down.
11. Cut sixteen inches of the faux suede cord and onto it thread the remaining brass and silver jump rings.
12. Thread one end through one of the brass jump rings on your beaded segment, and thread the other end through the other jump ring at the other end of your beaded segment.
13. Bring the ends of your cord back up through the jump rings on the strand, each passing through three jump rings.
14. Pull both ends of the cord until the tips are about one inch away from each other.
15. Tie each end around itself in a simple knot so that you may make the bracelet adjustable by sliding the knots closer or farther away from each other.