

Black Bullion Bracelet

Project B8026

Alexandra Smith

This bracelet combines flattened gold plated curb chain and black faux suede in a striking cross-stitch pattern that is quick and easy to weave.

What You'll Need

TierraCast 22K Gold Plated Lead-Free Pewter 3/4 Inch Anna's Toggle Clasp (1)

SKU: FCL-7138

Project uses 1 piece



Gold Plated Bulk Chain, Heavy Flattened Curb Links 9.5x12.5mm, 1 Inch, Bright Gold

SKU: CHX-08014

Project uses 13 pieces



22K Gold Plated Open Jump Rings 10mm 18 Gauge (50)

SKU: FJR-5210

Project uses 2 pieces



Beadsmith Black Faux Leather Suede Beading Cord 9Ft (3 Yd) Spool

SKU: XCR-43100

Project uses 5 feet



G S Hypo Cement Precise Applicator Essential!

SKU: XTL-1001

Project uses 1 piece



Recommended Tools:

[XTL-4012] Beadalon Tying Station Tool, for Shamballa and Wrapped Bracelets, 1 Piece,

[XTL-5514] Beadsmith Jewelry Fine Round Nose Micro Pliers, [XTL-5511] Beadsmith

Jeweller's Micro Pliers Chain Nose Flat Nose, [XTL-5600] Xuron Sharp Flush Cutter Pliers -

Wire/Soft Flex



Instructions

This bracelet fits a 6.5 inch wrist. For a longer bracelet, add additional jump rings to each end when attaching the clasp. In addition to the materials listed, you will need some thread to use with your tying station.

1. Begin by identifying the centermost link of your 13 inch section of curb chain, and note where the seam on the link is located.
2. Use two pairs of sturdy flat or chain nose pliers to grip the center link on either side of the seam. Open the link the same way you would open a jump ring to separate the two lengths of chain you will use for your project.
3. Please watch our video: [How to Make a Cross Style Chain Woven Bracelet](#). In this video, you will see from start to finish how to create this bracelet using 3mm faux leather and thick flattened curb chain. You will also see how to tie off the cord and attach a clasp.